

TY BY 191039087.009-2017

## СКП

Power supports are designed for aerial cable supply, SIW lines, siting of advertising and other structures.

Power poles can be used for: lighting of highways, routes, roads and streets, SIW pulling between towns and villages.

### DESIGN:

Power faceted support – buried;  
Support shaft 8 -12 m high

### PROTECTIVE COATING

Model СКП(о) – hot zinc coating.

Model СКП(хц) – cold zinc coating.

Color on request (according to the international RAL palette).

### EQUIPMENT:

1. Cable – on request
2. Entry panel (see pages 104-105) – on request

PARAMETER SHEET СКП (FACETED)

Name	H	h1	D1	D2	Thickness	masa
	М	М				
СКП-8-0,25	8	2	100	280	4	215
СКП-8-0,4	8	2				215
СКП-8-0,7	8	2				257
СКП-8-1,0	8	2				257
СКП-8-1,3	8	2	160	360	6	432
СКП-8-1,5	8	2				432
СКП-8-1,8	8	2				432
СКП-8-2,0	8	2				571
СКП-8-2,2	8	2			8	571
СКП-9-0,25	9	2	100	270	4	226
СКП-9-0,4	9	2				254
СКП-9-0,7	9	2				417
СКП-9-1,0	9	2				470
СКП-9-1,3	9	2	160	360	6	470
СКП-9-1,5	9	2				491
СКП-9-1,8	9	2				491
СКП-9-2,0	9	2				650
СКП-9-2,2	9	2			8	650
СКП-10-0,25	10	2	100	320	4	282
СКП-10-0,4	10	2				419
СКП-10-0,7	10	2				497
СКП-10-1,0	10	2				497
СКП-10-1,3	10	2	160	350	6	657
СКП-10-1,5	10	2				672
СКП-10-1,8	10	2				672
СКП-10-2,0	10	2				703
СКП-10-2,2	10	2			8	703

